BCV-20120



## Description

- > With an integrated LiFePO4 battery, the E-Box offers you an all-in-one solution for your vehicle's energy autonomy.
- Specially designed to fit under the passenger seat, this battery covers all the electrical needs of the adapted cell while taking up minimal space.
- As an optional feature, you can also integrate the 12V distribution panel.



BCV-15120

## **Features**

## > Fully integrated

A single box containing the LiFePO<sub>4</sub> battery, the DC/DC charger, the AC/DC charger, the MPPT solar charge controller and the DC/AC converter.

- More powerful and longer-lasting Provides twice as much power as a lead battery while maintaining a high energy capacity. Up to 4000 cycles at 0.5 C charge and discharge.
- Wide temperature range
   TOperating temperature ranging from -20 °C to 60 °C.
- > Power supply prioritisation

Thanks to the Box ACE Energy's built-in power prioritisation board, you can automatically manage the  $230V_{\rm AC}$  power supply when the vehicle is connected to the power supply via the external outlet.

## > Communication

Control the battery charging level and status via a dedicated mobile app.

AC =	100Ah batteries version 1.0.0				
75 %					
<b>13.37 V</b> Voltage	+ 10.3 A Current				



	Refere	ence	10310-1500W	10310-2000W
Technical	Nomir	nal voltage	12.8V	
features	Nomir	nal capacity	120Ah	
	Full ba	attery voltage	14.6V	
	Rated	power	1530Wh	
	Intern	al resistance	≤30mΩ	
	Charg	e current	≤100A	
	Disch	arge current	150A	200A
	Peak o	current	300A	400A
	Usefu	llife	≥4000 cycles	
	Self-d	ischarge	<3%	
DC-DC charger	Applic	able voltage	12-16V	
	Charg	e current	50 to 70A (dedicated line)	
	Auton	natic D+ detection	Optional	
AC-DC charger	Applic	icable voltage 230-240V <sub>AC</sub> / 50Hz		<sub>sc</sub> /50Hz
	Charg	rge current 20A		4
Solar charger	Applic	able voltage	≤80V	
	Charge current		20A	
	Maxim	num power	290W	
DC-AC converter	Outpu	it voltage	230-240V <sub>AC</sub> /50Hz	
	Rated	power	1500W	2000W
	Peak	power	3000W	4000W
Mechanic	Materials		ABS + PEHD	
	Dimensions		350 x 370 x 210 mm	
	Weight		25kg	
Communication	Bluetooth 4.2		Android and iOS mobile app	
Certification		Battery pack	E57*10R06/02*085*00	
	R10	DC/DC 50A charger	E57*10R06/00*0112*00	
		Converter	E57*10R06/05*570*00	







Auxiliary battery
Increase your capacity to 240Ah
with auxiliary battery
Ref. ACE-AUXI20

