BCV-20120



Description

- > With an integrated LiFePO4 battery, the E-Box offers you an all-in-one solution for your vehicle's energy autonomy.
- Specially designed to fit under the passenger seat, this battery covers all the electrical needs of the adapted cell while taking up minimal space.
- As an optional feature, you can also integrate the 12V distribution panel.



BCV-15120

Features

> Fully integrated

A single box containing the LiFePO₄ battery, the DC/DC charger, the AC/DC charger, the MPPT solar charge controller and the DC/AC converter.

- More powerful and longer-lasting Provides twice as much power as a lead battery while maintaining a high energy capacity. Up to 4000 cycles at 0.5 C charge and discharge.
- Wide temperature range
 TOperating temperature ranging from -20 °C to 60 °C.
- > Power supply prioritisation

Thanks to the Box ACE Energy's built-in power prioritisation board, you can automatically manage the $230V_{\rm AC}$ power supply when the vehicle is connected to the power supply via the external outlet.

> Communication

Control the battery charging level and status via a dedicated mobile app.

AC =	100Ah batteries version 1.0.0
75	5 %
13.37 V Voltage	+ 10.3 A Current



	Refere		10310-1500W	10310-2000W
Technical features		nal voltage		
reatures	Nomir	nal capacity	120Ah	
	Full ba	attery voltage	14.6V	
	Rated	power	1530Wh	
	Intern	al resistance	≤30mΩ	
	Charge current		≤100A	
	Discha	arge current	150A	200A
	Peak o	current	300A	400A
	Useful	life	≥4000 cycles	
	Self-di	ischarge	<3%	
DC-DC charger	Applicable voltage		12-16V	
	Charg	e current	50 to 70A (dedicated line)	
	Automatic D+ detection		Optional	
AC-DC charger	Applicable voltage		230-240V _{AC} / 50Hz	
	Charg	e current	20A	
Solar charger	Applicable voltage Charge current Maximum power		≤80V	
			20A	
			290W	
DC-AC converter	Output voltage		230-240V _{AC} / 50Hz	
	Rated	power	1500W	2000W
	Peak p	power	3000W	4000W
Mechanic	Materials		ABS + PEHD	
Dimensions Weight		nsions	350 x 370 x 210 mm	
		25kg		
Communication	Bluetooth 4.2		Android and iOS mobile app	
Certification		Battery pack	E57*10R06/02*0853*00	
	R10	DC/DC 50A charger	E57* 10R06/00*0112*00	
		Converter	E57* 10R06/0	5*0570*00



iOS iOS mobile app



Auxiliary battery
Increase your capacity to 240Ah
with auxiliary battery
Ref. ACE-AUXI20

